




PLĀTNES Nr.3 STIEGROJUMA PLĀNS




GRIEZUMS 2-2




STIEGROJUMA SPECIFIKĀCIJA

Poz.	Diametrs(mm), Tērauda klase	Garums (mm)	Stiegru skaits (gab.)	Kopējais garums (m)	1m svars (kg)	Kopējais svars (t)
No						
1	Ø 12, Bst500s	1840	21	38.6	0.89	0.034
2	Ø 8, Bst500s	2510	7	17.6	0.6	0.011
3	Ø 12, Bst500s	2100	13	27.3	0.89	0.024
4	Ø 16, Bst500s	2100	6	12.6	1.58	0.020
5	Ø 8, Bst500s	640	42	26.9	0.6	0.016
6	Ø 8, Bst500s	880	17	15.0	0.6	0.009
7	Ø 16, Bst500s	2100	8	16.8	1.58	0.027
8	Ø 8, Bst500s	320	16	5.1	0.6	0.003
9	Ø 8, Bst500s	170	20	3.4	0.6	0.002
	KOPĀ					0.146

GRIEZUMS 1-1



GRIEZUMS 3-3



PIEZĪMES:

DIMENSĪJAS: • VISI IZMĒRI DOTI MILIMETROS, AUGSTUMU ATZĪMES - METROS

- LENĶĶI - GRĀDOS (0 - 360)

APZĪMĒJUMI: _____ AUGŠĒJAIS STIEGROJUMS

APAKŠĒJAIS STEIGROJUMS

NORĀDĪJUMI

- MINIMĀLAIS BETONA AIZSARGKĀRTAS BIEZUMS VIRS STIEGROJUMA - 40mm
- RASĒJUMU SKATĪT KOPĀ AR RAS. BK-dzk-001.

[illegible]